

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (currently amended) A ~~P~~refilled medical syringe ~~for medical purposes with comprising:~~

a syringe barrel (3) enclosing an inner space (5);_i with

a syringe plunger (9) disposed ~~therein~~ in the space and displaceable with a plunger rod (11) ~~provided with~~ having an outer thread (29);_i with

an end plug (15) closing off ~~the~~ an cannula end of the syringe barrel (3), ~~said the~~ the end plug having a through-channel (17) closed off by a membrane (19);_i with

a finger support (13) disposed on ~~the~~ an end of the syringe barrel (3) opposite the end plug (15) and ~~provided with~~ having a through-opening (49) for the plunger rod (11);_i and with

a thread system (25) that cooperates with the plunger rod (11) and with the finger support (13);_i ~~and which comprises~~ the thread system having a thread sleeve (27) ~~provided with an internal thread (59) that cooperates with the~~ an outer thread (29) on the plunger rod (11), ~~characterized in that~~ the thread sleeve (27) ~~is detachably~~ being detachable connected with the finger support (13) and ~~together~~ coupled with the plunger rod (11) ~~can be displaced for common displacement~~ into the inner space (5).

2. (currently amended) The ~~S~~yringe ~~as defined in~~ of claim 1, ~~characterized in that~~ wherein the thread sleeve (27) is pressed into the base of the finger support (13).

3. (currently amended) The ~~S~~yringe ~~as defined in~~ of claim 1-~~or~~ 2, ~~characterized in that~~ wherein the thread sleeve (27) is coupled with the finger support (13) in a positively locking manner.

4. (currently amended) The Ssyringe ~~as defined in one of the preceding claims of claim 1, characterized in that~~ wherein there is provided a pin (23) that can be brought into contact with the membrane (19).

5. (currently amended) The Ssyringe ~~as defined in one of the preceding claims, characterized in that~~ of claim 1, wherein the thread system (25) is configured as a separate part.